

Blackmagic Web Presenter



Blackmagic Web Presenter makes any SDI or HDMI video source appear as a USB webcam for higher quality web streaming using software such as Skype or streaming platforms such as YouTube Live, Facebook Live, Twitch.tv, Periscope and more! Blackmagic Web Presenter includes 12G-SDI and HDMI inputs, XLR microphone input, HiFi audio input, Teranex quality down conversion and a 2 input live switcher when used with the optional Teranex Mini Smart Panel.

Connections

SDI Video Inputs

1

SDI Video Outputs

1x program out, 1x loop out.

SDI Rates

270Mb, 1.5G, 3G, 6G, 12G

HDMI Video Inputs

1

HDMI Video Outputs

1x loop out

Analog Video Inputs

None

Analog Video Outputs

None

Analog Audio Inputs

1x XLR.2 x RCA HiFi.

Analog Audio Outputs

None

Timecode Connection

None

Reference Input

None

RCA

2 X HiFi Analog audio input

XLR

1 X input supporting both microphone and line levels

USB Webcam

1

HDMI 2.0


1 X Input, 1 X loop out, (2 channel embedded audio)

USB 2.0

1 X Type B

Mini USB

1 X for software updates



Standards

Streaming Video Standards

720p over USB.

HDMI Video Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60
 1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p50,
 1080p59.94, 1080p60
 1080i50, 1080i59.94, 1080i60

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
 2160p29.97, 2160p30, 2160p50,
 2160p59.94, 2160p60

12G SDI Video Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60
 1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p50,
 1080p59.94, 1080p60
 1080PsF23.98, 1080PsF24,
 1080PsF25, 1080PsF29.97, 1080PsF30
 1080i50, 1080i59.94, 1080i60

2K Video Standards

None

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
 2160p29.97, 2160p30, 2160p50,
 2160p59.94, 2160p60

4K Video Standards

None

Hardware Frame Buffer

Supports any USB UVC and UAC webcam video drivers.

Computer Capture

USB webcam for Mac, Windows, Linux and any operating system that supports 720p HD webcams.

Control

Basic Settings Control

Mini Switches.

Built in Control Panel

None. Supports Teranex Mini Smart Panel with 2.2 inch color display for video preview, audio meters and status.

Optional Front Panel Control

Front mounted Smart Panel with LCD, rotary knob and six settings buttons

Device Control

None

Software

Compatible Services and Software

YouTube Live, Facebook Live, Twitch.tv, Periscope, Skype, Open Broadcaster and XSplit Broadcaster.

Operating Systems



macOS 10.12 Sierra,
macOS 10.13 High Sierra or later,



Linux



Windows 8.1 or Windows 10.



Chrome OS

Power Requirements


Power Supply

1 x Internal 90-240V AC.

Power Consumption

24 watts

Physical Specifications



Environmental Specifications

Operating Temperature:

5° C to 50° C (41° - 122° F)

Storage Temperature:

-20° to 60° C (-4° to 140° F)

Relative Humidity:

0% to 90% non-condensing

What's Included

Web Presenter

SD card with software and manual

Warranty

3 year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2017, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller